## SATCO NUVO

Project Name

Location

Prepared By



N	ot	6	9
ш	v.	·	9

40W/LED/HID/WP/3K/E39/100-277V

General	
Status	Active
Watts	40
HID Equivalent	250
Volts	100V-277V
Shape	Corncob
Base	Mogul
ANSI Base	E39
Finish	Un-Lensed
CCT (Kelvin)	3000
Temperature	Warm White
CRI	85
Lumens	5600
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length 11 in. Width 8 in. Depth 8 in.
Ballasting Requirements	Direct wire voltage range 100-277V
Electrical	
	50/60 Hz
Operating Frequency	50/60 Hz N/A
Operating Frequency Dimming Type Power Factor	N/A 0.91
Operating Frequency Dimming Type	N/A
Operating Frequency Dimming Type Power Factor Burning Position	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature Physical	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information  Enclosure Rating	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical  MOL  MOD Housing Color  Additional Information  Enclosure Rating Warranty	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information Enclosure Rating Warranty  Compliance	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp 5 Year Limited - Hi-Pro
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information  Enclosure Rating Warranty  Compliance Safety Listing	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp 5 Year Limited - Hi-Pro
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information Enclosure Rating Warranty  Compliance Safety Listing Location Rating	N/A  0.91  Horizontal Operation  -29C (-20F) to a maximum of +60C (+140F)  10.63  3.56  White  Enclosed Rated Lamp  5 Year Limited - Hi-Pro  cULus Classified  Damp
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information  Enclosure Rating Warranty  Compliance Safety Listing Location Rating Energy Star	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp 5 Year Limited - Hi-Pro  cULus Classified Damp No
Operating Frequency Dimming Type Power Factor Burning Position Operating Temperature  Physical MOL MOD Housing Color  Additional Information  Enclosure Rating Warranty  Compliance Safety Listing Location Rating Energy Star DLC Approved	N/A 0.91 Horizontal Operation -29C (-20F) to a maximum of +60C (+140F)  10.63 3.56 White  Enclosed Rated Lamp 5 Year Limited - Hi-Pro  cULus Classified Damp No Yes



















